

HV675

MediaPlay

Introduction

The new HV675 supports high definition video output (up-scaling to 1080I) for better picture quality, and it supports standard USB External Storage for the ever-increasing storage demand of digital contents.

The HV675 is compatible with NTFS / FAT32 file system. User can connect it with a USB External Storage loaded with home video, music, and photos, and then immediately playback the contents on TV.

The HV675 features the most powerful DivX external subtitle support. Furthermore, the complete DVD menu support, photo viewer with thumbnail preview, and Music Slideshow function, all makes it the most convenient choice for consumer's digital home theater system.

Feature Highlights

- Turn your USB HDD & Flash Drive into Media Player
- Compact and Light Weight Design
- Supports USB External Storage Playback
- HDMI Connection
- Video Up-scaling to 1080i
- Digital photo @ HD resolution
- Play DVD folder
- Support complete DVD function including DVD menu
- Digital photo viewer with thumbnail preview
- Music Slideshow
- The most powerful **DivX** subtitle display feature
- Supports **FAT32 / NTFS** file systems



Specifications

STORAGE	
Storage Media	USB HDD/ USB Flash Drive (Minimum 512MB or larger) (USB card readers not supported)
File System	NTFS / FAT32 (Minimum Allocated Unit Size 4096 bytes)
INTERFACE	
USB 2.0	USB type A connector x 1
AUDIO/VIDEO INTERFACE	
Analog	Composite video and stereo audio out jack x 1 (diameter: Ø3.5, composite cable included)
	Component video jack (Y/Pb/Pr) x 1 (diameter: Ø3.5, component video cable included)
Digital	HDMI connector x 1
	Coaxial S/PDIF Output (RCA x 1)
MEDIA SUPPORT	
Media Type	MPEG-1, MPEG-2, DivX 3.11/4.x/5.x, Xvid, JPEG, MP3, WAV
File Extension	dat, mpg, mpe, mpeg, vob, m2p, avi, divx, xvid, jpg, jpe, jpeg, mp3, wav
DVD Folder	DVD Menu/Audio/Subtitle/Angle Selection
DivX Subtitle Format	IDX / SUB, SRT, ASS, SSA, SUB (type II), SMI, PSB
MAX. CONTENT RESOLUTION	
Video	720 x 576 pixels
JPEG	5120 x 3840 pixels (baseline)
MP3	320kbps
IDX/SUB	480i / 576i / 480p / 576p
VIDEO OUTPUT	
TV Standard	NTSC / PAL
Screen Ratio	4:3 / 16:9
Component	NTSC-480i/480p / PAL-576i/576p / 720P(50/60Hz) (upscaling)/ 1080I(50/60Hz) (upscaling)

HDMI	720P(50/60Hz) (upscaling)/ 1080I(50/60Hz) (upscaling)
AUDIO OUTPUT	
Analog Audio	Stereo / Left Mono / Right Mono
Digital Audio	Dolby Digital 5.1 / DTS pass through
POWER SUPPLY	
Input	AC 100~240V 50/60Hz
Output	DC 5V, 2A
GENERAL	
Dimensions	130(W) x 24(H) x 84(D) mm 5.1(W) x 0.9(H) x 3.3(D) inch
Weight	124g / 4.37 oz
MISC	
Connector Adapter	SCART adapter x 1 (Europe only)
OSD Language Support	English, French, German, Italian, Spanish, Portuguese, Russian, Polish, Czech, Hungarian, Traditional Chinese, Simplified Chinese, Japanese.
Subtitle Code Page Support	Latin1, Latin2, Baltic, Standard Cyrillic, Turkish, Greek, Arabic, Traditional Chinese, Simplified Chinese, Japanese.



*Specs are subject to change without notice.